

DT-PRIMER



“The Innovating Company”

PRODUCT DESCRIPTION

DT-PRIMER is an entirely new concept in primers for cementitious materials. Because it’s extremely small particle allows it to travel past where most primers stop, it penetrates the substrate to latch onto the concrete or overlay deep inside the matrix, thus creating a better surface for the overlay to bond to. DT-Primer increases the bond strength by creating a more efficient chemical link between the concrete and the overlay, and by providing a clean, dry surface for the overlay to attach to.

ADVANTAGES:

- It penetrates deeply into the sub floor.
- Very easy application.
- Greatly enhances bonding to concrete.
- Prevents the sub floor from absorbing moisture from overlay.
- May be applied on interior or exterior floors.
- Great for priming all masonry surfaces: concrete, tile, terrazzo, brick, and overlays.
- Dries quickly.

DT-PRIMER is a ready to use product. It should not be diluted.

SURFACE PREPARATION:

Surface must be clean and free of contaminants, old polishes must be removed, floor must be completely dry before application. New concrete should be cured for at least 14 days. The floor should be adequately profiled via mechanical or chemical means to ensure proper bonding.

APPLICATION:

Always test small area for compatibility and satisfactory bonding. Do not apply if ambient temperature is below 40 degrees. DT-Primer is compatible with all DecoTop products and most other overlays. Once surface is properly prepared and dry, apply DT-Primer with a roller, spray, mop or any other appropriate tool. Apply evenly over entire surface, do not leave puddles.

Apply a thin coat; if surface is very porous, a second coat may be necessary.

COVERAGE:

Five gallon of DT-Primer should cover between 800 to 1200 square feet. Coverage will vary according to the porosity and composition of the floor material. DT-Primer will dry to touch in about 30 minutes (more time maybe needed in low temperatures) and it must be fully dry before applying Overlay. Drying conditions will vary according to humidity, airflow, temperature and thickness of the application.

DT-PRIMER PROPERTIES

Coverage	160-200 square feet/gallon
Drying time	30 - 60 minutes
Leveling	Excellent
pH	8.0 - 90
Powdering resistance	Excellent
Recoat	Very good
U.L.Approved.....	Yes
Shelf life	1 year
Specific gravity	1.04

PACKAGING:

- 1 Gallon (3.8 L) jugs
- 5 Gallon (18.9 L) pails
- 55 Gallon (208 L) drums

WARRANTY: DECOSUP DT-PRIMER is warranted to be of uniform quality within manufacturing tolerances. Since control is not exercised over its use, no warranty, expressed or implied, is made as to the effects of such use. Seller and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective



Made in USA
For professional use only
Consult Material Safety Data Sheet before use.