

DECOSUP LIQUID RELEASE

PRODUCT DESCRIPTION

DECOSUP LIQUID RELEASE is a blend of evaporating, residue free release agents for use in the imprinting process to allow the clean release of texturing tools from concrete or overlay surfaces.

FEATURES AND BENEFITS:

Allows a clean bond break between fresh concrete or overlay and stamping mats.
Allows the contractor to correct mistakes as they stamp the surface.
It is residue free.
It can be troweled on.
Concrete can be sealed with water base or solvent base sealer

DIRECTIONS FOR USE:

STAMPED CONCRETE:

After the concrete has been colored and is ready to be stamped, wet stamping mats once with DECOSUP Liquid Release, and using a pump sprayer apply release over area to be immediately stamped. Do not get too far ahead as the release will evaporate and a second application may be needed. Stamp as usual, and if you see any mistakes as you stamp, you can re-trowel and re-stamp the area if needed. Apply freely and as much as you need. Allow to evaporate and then antique or seal as desired.

STAMPED OVERLAYS:

After polymer overlay is set enough wet stamping mats with DECOSUP Liquid Release and spray with a pump sprayer over area to be immediately stamped, do not get too far ahead as the release will evaporate, and a second application may be needed. Stamp as usual, and if you see any mistakes as you stamp, you can re-trowel and re-stamp the area if needed. Apply freely and as much as you need. Allow to evaporate and then antique or seal as desired.

MAINTENANCE:

It is highly recommended to develop and follow a routine maintenance schedule for all colored concrete so that it will maintain a top quality appearance. Every 24 to 60 months, colored concrete installations should be inspected, cleaned and resealed as required by volume and intensity of traffic. The need will depend on a number of factors including traffic conditions, geographical location and weather.

LIMITATIONS:

Inconsistencies in job site conditions, finishing practices, and curing methods may produce variations in the color of the finished product

COVERAGE:

800 to 1000 square feet per 5 Gallon pail.

CAUTION: This product should be handled with care. For more information please see **DECOSUP LIQUID RELEASE MSDS**.

WARNING: READ COMPLETE MATERIAL SAFETY DATA SHEET BEFORE APPLICATION AND USE. This is a combustible liquid. May cause skin, eye or respiratory irritation during its application and use. Keep away from flames or heaters, use in a well-ventilated area. Do not take internally. Do not get into eyes, skin or clothes, wear a NIOSH approved respirator, protective clothing and gloves, keep away from children..

WARRANTY: DECOSUP LIQUID RELEASE is warranted to be of uniform quality within manufacturing tolerances. Since control is not exercised over its use, no warranty, expressed or implied, is made as to the effects of such use. Seller and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective.